
No.	ITEM#	DESCRIPTION	QTY.	NOTES
1	10120-3000VE	CONNECTOR	1	3M
2	10320-52A0-008	HOOD	1	3M
3	JZSP-CMP9-2	CONNECTOR, MFG#: 54280-0600	1	MOLEX
4	T/20276-SB	CABLE, 22AWG x2C, 24AWG x2P, SHIELDED	-	TAIYO



NOTES:

A CONNECT SHIELD TO CONNECTOR SHELL


B YASKAWA INFORMATION LABEL :

YASKAWA
"ITEM NUMBER" ("REV")
"VENDOR CODE" "MM/YY"


C ADD APPROPRIATE HEAT SHRINK TUBE, USE GROMET IF NEEDED

D USING AUTOMATED OR MANUAL CABLE TESTER, VERIFY ALL CONNECTIONS, AND VERIFY THAT EACH WIRE OR TERMINATION IS NOT SHORTED TO ANY OTHER WIRE OR TERMINATION UNLESS INTENDED TO BE ELECTRICALLY CONNECTED. ALL WIRES OR TERMINATIONS SHALL BE ISOLATED FROM ALL OTHER WIRES OR TERMINATIONS BY A MINIMUM OF 10 MEGOHM AT 500VDC. RECORDS OF TEST MUST BE MAINTAINED AND PROVIDED UPON REQUEST.

E CONDUCT HI-POT TEST AT 600 VAC FOR 1 SECOND.
(NOTE: LEAK CURRENT = 20 mA)



ITEM NUMBER	X = LENGTH
AFAHCE-03(A)	3 m
AFAHCE-05(A)	5 m
AFAHCE-10(A)	10 m
AFAHCE-15(A)	15 m
AFAHCE-20(A)	20 m
AFAD-P2(A)	0.2 m



CABLE SPECIFICATION (mm)	
OUTER DIAMETER	6.5
BENDING RADIUS	N/A
STANDARD	UL/CE
UL/IP CLASSIFICATION	
CONNECTOR (1)	UL94V-0
CONNECTOR (2)	UL94V-0

0 INITIAL RELEASE			EAR 2006-016

DESIGN: -	-	MATERIAL: SEE PART LIST ABOVE	YASKAWA Energy In Motion™
DRWN: D.GREULOCH	4/06/06	SPEC: SEE PART LIST ABOVE	
CHKD: N.HOUCK	5/1/06	FINISH: N/A	
TECH: -	-	TOLERANCES/REFERENCES: UES000002	TITLE: SGMAH Encoder Cable for FSP
APRV: C.KINTNER	5/2/06		
THIS DOCUMENT AND INFORMATION CONTAINED IN IT ARE CONFIDENTIAL, AND CANNOT BE COPIED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF YASKAWA ELECTRIC AMERICA INC.		MODEL(S): SGMAH	DWG: UWR00651
		REF DWG: JZSP-CMP00-XX(A)	
		DIMENSIONS: mm SCALE: NTS	ITEM #: *SEE CHART
		SIZE: B SHEET: 1/1	

efesotomasyon.com